

MATERIAL SAFETY DATA SHEET

CREATEX™
COLORS

 14 Airport Park Road
 P.O. Box 120
 East Granby, CT. 06026
 (860) 653-5505
 (860) 653-0643 fax

PRODUCT IDENTIFICATION
REVISION DATE: 8/01/12

| | |
|---|---|
| IDENTITY: (As used on label) | Synonyms: |
| Creutex Colors – Retarder Item # 5607 | |
| Chemical family: | Formula |
| --- | Aqueous dispersion of organic pigment and acrylic polymer |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|--|-------|---|----------|
| Not a hazardous material as outlined by the OSHA Hazard Communication Standards. Meets ASTM D-4236 Standards | | | |
| | | | |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Water expendable |
| Vapor pressure (mm Hg): NA |
| Vapor density: 1 |
| Specific Gravity (H₂O-1): 1.1 |
| Evaporation Rate: (BuAct=1): 1 |
| V.O.C. : 0.42 lbs/gal |

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
|--|

REACTIVITY DATA

| |
|---|
| Stability: (X) Stable () Unstable Conditions to avoid: extreme temperatures, open flames |
| Incompatibility (materials to avoid) : N/A |
| Hazardous Decomposition or Byproducts: N/A |
| Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: None |

HEALTH INFORMATION

| |
|---|
| Primary Route of Exposure: Inhalation: Skin: X Ingestion: Eyes: |
| Carcinogen: IARC: no NTP: no OSHA: no |

Signs and Symptoms of Exposure:

none found

Medical Conditions Generally Aggravated by Exposure:

none found

Emergency and First Aid Procedures:

Eye Contact, remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.

Ingestion, If victim is conscious give water, *do not* induce vomiting. Call physician.

SPECIAL PROTECTION DATA

Respiratory Protection:

Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.

Ventilation:

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.

Protective Gloves:

Neoprene or rubber gloves with cuffs

Other Protective Clothing:

Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

SPILL AND LEAK PROCEDURES

Storing/Handling:

Store in tightly closed containers in a cool, well-ventilated area.

Waste Disposal Method:

Sanitary landfill in accordance with local, state, and federal regulations.

Other Precautions:

None