

CRX2017-268
September 29, 2017
Page 1

1. Identification of the Preparation and of The Company

Product Name and/or Code: Auto Air Colors™ Quicksilver W357

Auto Air Colors™ Gold Plating W358

Effective Date: 29-Sep-17

Manufacturer: Color Craft Ltd/ Createx Colors/ Auto-Air Colors

14 Airport Park Road, PO Box 120

East Granby, CT 06026

Information Contact: 860-653-5505

860-653-5505

Emergency Contact: Contact your local Poison Control Center. Product Use: ART MATERIAL - Consumer Product.

2. Hazards Identification

Emergency Overview

WARNING! COMBUSTIBLE LIQUID AND VAPOR. IRRITANT.

Classification of the Product:

Label Elements Conforms to ASTM D-4236

①

Pictograms

Children's Statement

GHS07 GHS02

Signal Word WARNING!

Hazard Statement Causes eye irritation. May cause skin irritation.

Precaution Statement Keep away from heat, sparks and flame. Avoid contact with eyes and

skin. Wash thoroughly after handling. Close container after each use.

Use with adequate ventilation. Do not eat, drink or smoke when using

this product. Avoid breathing vapors or mist.

First Aid Statement In case of eye contact, flush immediately with plenty of water for at

least 15 minutes and get medical attention immediately; for skin, wash

thoroughly with soap and water. If you experience difficulty in

breathing, leave the area to obtain fresh air.

KEEP OUT OF THE REACH OF CHILDREN.

NFPA Health: 1

Flammability: 2

Reactivity: 0

HMIS Health: 1

Flammability: 2 Physical Hazard: 0



CRX2017-268
September 29, 2017
Page 2

Regulation (EC) No. 1272/2008

Studies have not been performed on this particular mixture. *The information below is based on data in the individual ingredients.*Acute Toxicity 4 H302; Acute Toxicity 4 H312; Skin Irritation 2 H315; Eye Irritation 2 H319; Acute Toxicity 4 H332; Flammable liquid 3 H225; STOT SE 3 H336; Eye Damage 1 H318; Skin Sensitizer 1 H317; Aquatic

3. Composition/Information on Ingredients:

Substances:

Mixture of the following chemicals: Water (CAS No. 7732-18-5) < 61.00 %

2- Butoxy ethanol (CAS No. 111-76-2) < 26.00%

Propan-2-ol (CAS No. 67-63-0) < 4.00%

BIT: 1,2 -Benzisothiazol-3(2H)-one, 1,2- Benzisothiazolin-3-one (CAS No.

2634-33-5) < 10PPM

Acute 1 H400.

Risk and Safety Phrases:

Ingredients are marked according to CLP Regulation (CLP-Regulation (EC) No 1272/2008) and no workplace-related occupational exposure limits are specified for any of the listed ingredients. These ingredients are regarded as trade secrets.

4. First Aid Measures					
Inhalation	If affected, remove to fresh air.				
Skin Contact	Wash the affected area thoroughly with plenty of soap and water.				
Eye Contact	Carefully flush with water for 15 minutes and get medical attention immediately.				
Ingestion	Drink water or milk to dilute. Do not induce vomiting. Contact a physician.				
5. Firefighting Measures					
Extinguishing Media	Water, foam, carbon dioxide or dry chemical equipment.				
Fire/Explosion Hazards	Combustible liquid and vapor.				
Flashpoint/Flammability	118°F. This product is combustible.				
6. Accidental Release Measures					
Environmental Precautions	Avoid release to the environment. Studies have not been performed of this particular mixture.				
Methods and Materials for Containment and Cleaning up	t Contain spill. Recover as much as possible. Absorb remainder with a inert material. Place into closed container and store in a safe locatio to await disposal. Wash the spill area with soap and water.				

^{*} The remainder of the formulation is composed of non-hazardous ingredients.



CRX2017-268
September 29, 2017
Page 3

7. Handling and Storage

Safe Handling Use under ventilated conditions. Avoid eye and skin contact. For

personal protection, we recommend that employees wash thoroughly after handling product. Always wash before eating, smoking or using toilet facilities. Keep container closed when not in

use. Keep container upright to prevent leakage.

Storage Store between 50-100 deg. F., ideally 70 deg. F.

8. Exposure Controls/Personal Protection

Personal Protective Equipment Wear goggles where spills or splashing may occur. Wear water

resistant impervious gloves if handling bulk amounts.

Exposure Limits

Cubetoneo	CAS#	OSHA PEL		NIOSH REL	ACGIH
Substance		mg/m3	8 hr. TWA(ST) STEL (C) Ceiling	Up to 10 - hr. TWA (ST) STEL (C) Ceiling	8 hr. TWA (ST) STEL (C) Ceiling
2-Butoxy ethanol	111-76-2	240	20 PPM	5 PPM	20 PPM
Propan-2-ol	67-63-0	980	400 PPM (ST) 500 PPM	400 PPM (ST) 500 PPM	200 PPM (ST) 500 PPM
1,2 -Benzisothiazol-3(2H)-one, 1,2- benzisothiazolin-3-one	2634-33-5	NOT ESTABLISHED			

Respiratory and Ventilation Wear approved NIOSH/MSHA respirator if exposure to mist or vapor

exceed applicable PEL/TLV limits. Use in accordance with

manufacturer's use limitations and OSHA STANDARD 1910-34. Local

ventilation may be used to prevent routine inhalation.

Skin Protection Wear water resistant impervious gloves if handling bulk amounts.

Eye Protection Wear goggles where spills or splashing may occur.

9. Physical and Chemical Properties

Appearance Colored Paint

Physical State Liquid

VOC Content 36.1 g/L Regulatory

Solids percentage 5

Color Silver/Gold
Odor Acrylic-like.
Boiling Point Not determined.
Freezing Point Not determined.
State (pH) Not determined.
Specific Gravity Not determined.
Viscosity Not determined.

Flashpoint 118° F

Vapor Pressure Not applicable to this mixture.

Vapor Density <1
Solubility in Water Miscible



CRX2017-268 September 29, 2017 Page 4

10.	Stability	and I	Reactivity

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability Stable under recommended storage conditions.

Conditions to Avoid Elevated temperatures (>50°C) and freezing.

Incompatible Materials None known.

Eye Effects

Dermal Effects

Hazardous Decomposition Products No dangerous decomposition products known. Decomposition

products depend on conditions.

11. Toxicological Information

Health Effects: Studies have not been performed on this particular mixture. The

information below is based on data in the individual ingredients.

Oral 2-Butoxy ethanol: LD50 Rat: 300 - 2,000 mg/kg (literature value)

Propan-2-ol: No data available.

BIT: US 500.00000000 mg/kg body weight

Dermal 2-Butoxy ethanol: LD50 Rabbit: >1,000 - 2,000 mg/kg (literature value)

Propan-2-ol: No data available.

BIT: No data available.

Inhalation 2-Butoxy ethanol: LC50 (4h) Rat: 10 - 20 mg/l (literature value)

Propan-2-ol: No data available.

BIT: No data available.

Causes eye irritation.

May cause skin irritation.

Sensitization Effects None known for the usual and ordinary uses of this product.

Inhalation Effects May cause nose and throat irritation.

Ingestion Effects None known for the usual and ordinary uses of this product.

Additional Toxicological Information: When used and handled according to specifications, the product does

not have any harmful effects according to past experience and the

information provided by the manufacturer.

12. Ecological Information

Toxicity: Not expected to be harmful to the environment. Studies have not been

performed on this particular mixture.

Aquatic Toxicity BIT: 1,2-benzisothiazol-3(2H)-one, 1,2- benzisothiazolin-3-one is a

substance known to be very toxic to aquatic life.

Persistence and Degradability

Bio Accumulative Potential

Mobility in Soil

Additional Ecological Information

No information available.

No information available.

No information available.



CRX2017-268
September 29, 2017
Page 5

13. Disposal Considerations

Dispose of all waste material in accordance with all applicable federal, state and local regulations for the disposal of aqueous polymer wastes.

14. Transport Information

DOT Non-Bulk This regulation does not apply to the non-bulk material.

Shipping Name Not regulated.
Technical Shipping Name Not regulated.
Hazard Class Not regulated.
UN Number Not regulated.
Packing Group Not regulated.

IMDG UN-No. UN1263

Proper Shipping Name UN-No. UN1263 PAINT RELATED MATERIAL

Hazard Class 3
Packing Group Packing Group III

Description UN1263 PAINT RELATED MATERIAL (48°C cc)

ICAO/IATA UN-No. UN1263

Proper Shipping Name UN-No. UN1263 PAINT RELATED MATERIAL

Hazard Class 3
Packing Group Packing Group III

Description UN1263 PAINT RELATED MATERIAL

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the materials.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture.

SARA Not applicable to this mixture.

Section 355 (extremely hazardous Not app

substances)

Not applicable to this mixture.

Section 313 (Specific toxic chemical listing Not applicable to this mixture.

TSCA (Toxic Substance Control Act)

All ingredients are listed.

Proposition 65 WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

As of September 15, 2017, this product contains listed substances known to the State of California to cause cancer, birth defects or other



CRX2017-268 September 29, 2017

reproductive harm, at levels which would require a warning under the statute.

Carcinogenicity Categories

EPA (Environmental Protection Agency) Not applicable to this mixture.

TLV (Threshold Limit Value established by Refer to section 8.

ACGIH)

MAK (German Maximum Workplace

Concentration)

NIOSH (National Institute for

Occupational Safety & Health)

OSHA (Occupational Safety & Health

Administration)

Not applicable to this mixture.

Not applicable to this mixture.

Not applicable to this mixture.

16. Other Information

Reason for Issue: New Product

Prepared by: Rudolph J. Jaeger, Ph.D., DABT, ERT (UK)

Chief Toxicologist and President ENVIRONMENTAL MEDICINE, INC.

778 CARVER AVENUE WESTWOOD, NJ 07675 jaegerr@envmed.com

201-666-7929 x13

The information contained in this Safety Data Sheet was compiled using the latest and most reliable information available to Color Craft Ltd./ Createx Color. The information is provided without any warranty, express or implied regarding its correctness or accuracy nor will Color Craft Ltd./ Createx Color. assume any liability for any loss or damage arising out of the use of this information including without limitation direct or indirect losses or expenses. To the extent permitted by law, no warranty express or implied regarding the product described herein shall be created by or inferred from any state or omission for this SDS. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.

Abbreviations and acronyms:

NFPA (SCALE 0-4) National Fire Protection Association (USA)

Health: 1 Caution: May be irritating.

Fire: 2 Caution: Combustible liquid flash point of 100°F to 200°F.

Reactivity: 0 Not reactive when mixed with water.

HMIS (SCALE 0-4) Hazardous Materials Identification System (USA)

Health: 1 Irritation or minor reversible injury possible.

Fire: 2 Materials which must be moderately heated or exposed to high

ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100°F but below 200°F. (Classes II

&IIIA)



CRX2017-268
September 29, 2017
Page 7

Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Reactivity: 0

H Statements

- H225 Highly Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very Toxic to aquatic life.

Exposure Limits

- TWA Time Weighted Average (8 hr.)
- STEL Short Time Exposure Limit (15 min.)
- REL Recommended Exposure Limit
- PEL Permissible Exposure Limit
- IDLH Immediately Dangerous to Life or Health